



The Os-series is a new digital high-speed camera designed to operate in the most demanding environments. The salient design feature of the Os 3 are its compact size combined with a wide data bus, making it capable of achieving very high frame rates (up to 3,000 fps) including transfer speeds to high-capacity solid-state (non-volatile) memory. Configurable DDR options include 16GB and 32GB.

KEY FEATURES

Maximum Resolution	1280 x 1024
Maximum FPS @ Maximum Resolution	3,000 fps
Image Storage @ Max Frame Rate (DDR 8)	7,723
Image Storage @ Max Frame Rate (DDR 16)	15,697
Image Storage @ Max Frame Rate (SSD 512)	9,447
Streaming FPS @ Max Resolution	320 fps
Maximum FPS	91,500 @ 1280 x 8
Minimum Exposure Time	1µs (100 ns with SI option)
Sensitivity ASA/ISO	6000 ISO Mono 2000 ISO Color
Power Requirements	18-36 VDC
Operating Temperature	-40+50°C / -40+122°F

SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 11.2 mm
Sensor Format	1.3 inch
Pixel Size (micron)	10.85x10.85 µm
Pixel Depth	12 bit mono 36 bit color

INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL

OUTPUTS

Sync	Frame sync / Strobe
HDSDI	Optional

FEATURES

Approx. Size	69 x 63 x 87 mm (W x H x L)
Approx. Weight	0.69 kg or 1.52 lbs
Shock/Vibration Rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	Optional
Mount	C-Mount standard , F Adaptor optional

SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF

COMMUNICATION

Ethernet	1000BaseT
----------	-----------



The Os-series is a new digital high-speed camera designed to operate in the most demanding environments. The salient design feature of the Os 3 are its compact size combined with a wide data bus, making it capable of achieving very high frame rates (up to 5,000 fps) including transfer speeds to high-capacity solid-state (non-volatile) memory. Configurable DDR options include 16GB and 32GB.

KEY FEATURES

Maximum Resolution	1280 x 1024
Maximum FPS @ Maximum Resolution	5,000 fps
Image Storage @ Max Frame Rate (DDR 8)	7,723
Image Storage @ Max Frame Rate (DDR 16)	15,697
Image Storage @ Max Frame Rate (SSD 512)	9,447
Streaming FPS @ Max Resolution	320 fps
Maximum FPS	152,000 @ 1280 x 8
Minimum Exposure Time	1 μ s (100 ns with SI option)
Sensitivity ASA/ISO	6000 ISO Mono 2000 ISO Color
Power Requirements	18-36 VDC
Operating Temperature	-40+50°C / -40+122°F

SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 11.2 mm
Sensor Format	1.3 inch
Pixel Size (micron)	10.85x10.85 μ m
Pixel Depth	12 bit mono 36 bit color

INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL

OUTPUTS

Sync	Frame sync / Strobe
HDSDI	Optional

FEATURES

Approx. Size	69 x 63 x 87 mm (W x H x L)
Approx. Weight	0.69 kg or 1.52 lbs
Shock/Vibration Rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	Optional
Mount	C-Mount standard , F Adaptor optional

SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF

COMMUNICATION

Ethernet	1000BaseT
----------	-----------



The Os-series is a new digital high-speed camera designed to operate in the most demanding environments. The salient design feature of the Os 3 are its compact size combined with a wide data bus, making it capable of achieving very high frame rates (up to 7,000 fps) including transfer speeds to high-capacity solid-state (non-volatile) memory. Configurable DDR options include 16GB and 32GB.

KEY FEATURES

Maximum Resolution	1280 x 1024
Maximum FPS @ Maximum Resolution	7,000 fps
Image Storage @ Max Frame Rate (DDR 8)	7,723
Image Storage @ Max Frame Rate (DDR 16)	15,697
Image Storage @ Max Frame Rate (SSD 512)	9,447
Streaming FPS @ Max Resolution	320 fps
Maximum FPS	213,570 @ 1280 x 8
Minimum Exposure Time	1µs (100 ns with SI option)
Sensitivity ASA/ISO	6000 ISO Mono 2000 ISO Color
Power Requirements	18-36 VDC
Operating Temperature	-40+50°C / -40+122°F

SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 11.2 mm
Sensor Format	1.3 inch
Pixel Size (micron)	10.85x10.85 µm
Pixel Depth	12 bit mono 36 bit color

INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL

OUTPUTS

Sync	Frame sync / Strobe
HDSDI	Optional

FEATURES

Approx. Size	69 x 63 x 87 mm (W x H x L)
Approx. Weight	0.69 kg or 1.52 lbs
Shock/Vibration Rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	Optional
Mount	C-Mount standard , F Adaptor optional

SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF

COMMUNICATION

Ethernet	1000BaseT
----------	-----------